

## High dynamic-range observation using a low-scattered light telescope PLANETS: design and feasibility study

# Masato Kagitani[1]; Takeshi Sakanoi[2]; Toshihisa Suzuki[3]; Yasuhiro Hirahara[4]; Yasumasa Kasaba[5]

[1] PPARC, Tohoku Univ; [2] Grad. School of Science, Tohoku Univ.; [3] Geophysics, Tohoku Univ.; [4] Earth&Planetary Sciences, Nagoya Univ.; [5] Tohoku Univ.

High dynamic-range (HDR) observation is one of the key technique to reveal composition, distribution and dynamics of plasma and neutrals in the vicinity of planets and their moons in our solar system, e.g. water plumes on Europa and Enceladus, volcanic plumes on Io, escaping plasma and neutrals from Venus and Mars, and so on. A low-scattered light telescope, PLANETS (Polarized Light from Atmospheres of Nearby Extra-Terrestrial Systems) would be an 1.8-m off-axis telescope on Mt. Haleakala, Hawaii under collaboration with Japan, USA, Germany, Brazil, and France. The off-axis optical system enables us to achieve HDR measurements without diffraction by support structure of secondary mirror. We present feasibility study of monitoring water plumes on Europa, neutral torus close to Enceladus, and ionosphere on Mars using PLANETS telescope.

To test feasibility of HDR under actual condition of wavefront error was made which includes by an optical system as well as by atmospheric turbulence, modeling the propagation of light though the system was made based on Fraunhofer (far-field) calculations with help from PROPER library (Krist 2007). The optical system consists of an entrance pupil (1.85 m), primary mirror, a deformable mirror, an occulting mask, a Lyot mask on a pupil, and a detector on image plane. We gave wavefront error made by atmospheric turbulence (Fried length is 25 cm for best 10% seeing condition) and the optical system represented with power spectral density. Then, dynamic range of point spread function was calculated for several cases of surface roughness of the primary mirror, 1 to 8 nm r.m.s., and number of control points for active wavefront compensation by a deformable mirror, 7 to 24. Finally we calculated brightness distribution of background continuum, and derived signal-to-noise ratio for each observing target assuming expected brightness and band-width of spectroscopy. For O<sup>2+</sup> 561 nm and N<sup>2+</sup> 391 nm emissions from Martian ionosphere and O 630 nm emission from Enceladus torus, sufficient signal-to-noise ratio is expected for 2-hour integration by employing wavefront compensation with 7x7 deformable mirror and small roughness of primary mirror, 2-nm r.m.s. Whereas for O 630 nm emissions from water plumes on Europa, wavefront compensation by 24x24 deformable mirror is needed to achieve sufficient signal-to-noise ratio for 2-hour integration.

We also present latest design of the telescope structure. The most part of the telescope structure is reuse of prototype of Kyoto 3.8-m telescope (Kurita and Sato, 2009) which employs commercial truss component for architecture. The structure is characterized by its light-weight and high-stiffness. The primary thin mirror (100 mm thick on edge) is supported by 36 points from bottom. The support structure is under examination by comparing an active support using force-control actuators against whiffle-tree with warping harnesses which both enable to compensate low-frequency wavefront error of the primary mirror. Latest design of the telescope as well as support structure of primary mirror will be presented.